

## Argon (refrigerated)

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: D-Ar-003B

Issue date: 4/1/2015 Revision date: 1/3/2023 Supersedes version of: 6/4/2019 Version: 4.4

## Warning



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name : Argon 4.6 liquid, Argon 5.0 liquid

SDS no D-Ar-003B

Other means of identification : Argon (refrigerated)

> CAS-No. : 7440-37-1 EC-No. : 231-147-0 EC Index-No.

: Listed in Annex IV / V REACH, exempted from registration. **REACH registration No** 

Chemical formula

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.

Test gas/Calibration gas.

Purge gas, diluting gas, inerting gas. Shield gas for welding processes.

Use for manufacture of electronic/photovoltaic components.

Laboratory use. Food applications.

Contact supplier for more information on uses.

Uses advised against Consumer use.

Uses other than those listed above are not supported, contact your supplier for more

information on other uses.

Attention: These products must not be applied to humans or animals unless they are

expressly designated as medical or medicinal gases!.

#### 1.3. Details of the supplier of the safety data sheet

Messer Industriegase GmbH GmbH

Messer- Platz 1

D - 65812 Bad Soden am Taunus

Germany

T 0049-(0)-6196 7760-200 - F 0049-(0)-6196 7760-280

SDB.de@messergroup.com - www.messer.de

## 1.4. Emergency telephone number

: Messer Produktionsgesellschaft Salzgitter GmbH +49 (0) 5341 21-9333, erreichbar Emergency telephone number

Montags 0:00 bis Sonntags 24:00

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards Gases under pressure: Refrigerated liquefied gas H281

Messer Industriegase GmbH Messer- Platz 1 D - 65812 Bad Soden am Taunus Germany, 0049-(0)-6196 7760-200

DE - en



## Argon (refrigerated)

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: D-Ar-003B

#### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS04

Signal word (CLP) : Warning

Hazard statements (CLP) : H281 - Contains refrigerated gas; may cause cryogenic burns or injury.

Precautionary statements (CLP)

- Prevention : P282 - Wear cold insulating gloves and either face shield or eye protection.

- Response : P336+P315 - Thaw frosted parts with lukewarm water. Do not rub affected area. Get

immediate medical advice/attention.

- Storage : P403 - Store in a well-ventilated place.

2.3. Other hazards

Asphyxiant in high concentrations.

The substance/mixture has no endocrine disrupting properties.

## SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Argon (refrigerated)	CAS-No.: 7440-37-1 EC-No.: 231-147-0 EC Index-No.: REACH registration No: *1	100	Press. Gas (Ref. Liq.), H281

Contains no other components or impurities which will influence the classification of the product.

## 3.2. Mixtures

Not applicable

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing

stopped.

- Skin contact : Adverse effects not expected from this product.

In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain

medical assistance.

- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.

- Ingestion : Ingestion is not considered a potential route of exposure.

### 4.2. Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation.

See section 11.

Messer Industriegase GmbH Messer- Platz 1 D - 65812 Bad Soden am Taunus Germany, 0049-(0)-6196 7760-200 DE - en

<sup>\*1:</sup> Listed in Annex IV / V REACH, exempted from registration.

<sup>\*3:</sup> Registration not required: Substance manufactured or imported < 1t/y.



## Argon (refrigerated)

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: D-Ar-003B

#### 4.3. Indication of any immediate medical attention and special treatment needed

None

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.

Product does not burn, use fire control measures appropriate for the surrounding fire.

- Unsuitable extinguishing media : Do not use water jet to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : None.

5.3. Advice for firefighters

: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat Specific methods

radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering

sewers and drainage systems. If possible, stop flow of product.

Use water spray or fog to knock down fire fumes if possible.

If leaking do not spray water onto container. Water surrounding area (from protected

position) to contain fire.

Move containers away from the fire area if this can be done without risk.

Special protective equipment for fire fighters : In confined space use self-contained breathing apparatus.

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire

fighters.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves

for firefighters.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

: Act in accordance with local emergency plan. For non-emergency personnel

> Try to stop release. Evacuate area.

Ensure adequate air ventilation. Use protective clothing.

Prevent from entering sewers, basements and workpits, or any place where its

accumulation can be dangerous.

See section 8 of the SDS for more information on personal protective equipment

For emergency responders : Wear self-contained breathing apparatus when entering area unless atmosphere is proved

Oxygen detectors should be used when asphyxiating gases may be released.

3/10

See section 5.3 of the SDS for more information.

6.2. Environmental precautions

Try to stop release.

Liquid spillages can cause embrittlement of structural materials.

## 6.3. Methods and material for containment and cleaning up

Ventilate area.

## 6.4. Reference to other sections

See also sections 8 and 13.

Messer Industriegase GmbH DE - en Messer- Platz 1 D - 65812 Bad Soden am Taunus Germany, 0049-(0)-6196 7760-200



## Argon (refrigerated)

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: D-Ar-003B

#### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Safe use of the product

: The product must be handled in accordance with good industrial hygiene and safety procedures.

Only experienced and properly instructed persons should handle gases under pressure.

Consider pressure relief device(s) in gas installations.

Ensure the complete gas system was (or is regularily) checked for leaks before use.

Do not smoke while handling product.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.

Avoid suck back of water, acid and alkalis.

Do not breathe gas.

Avoid release of product into work area.

Safe handling of the gas receptacle : Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Protect containers from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.)

designed to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a

wall or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating valve discontinue use and contact supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content of the container.

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

#### 7.2. Conditions for safe storage, including any incompatibilities

For more guidance on the safe storage of liquid oxygen, liquid nitrogen or liquid argon, refer to EIGA Doc.115 "Storage of Cryogenic Air Gases at Users Premises", downloadable at http://www.eiga.eu and consult your supplier.

Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps should be in place.

Containers should be stored in the vertical position and properly secured to prevent them from falling over.

Stored containers should be periodically checked for general condition and leakage.

Keep container below 50°C in a well ventilated place.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

### 7.3. Specific end use(s)

None.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

OEL (Occupational Exposure Limits) : None available.

DNEL (Derived-No Effect Level) : None available.

Messer Industriegase GmbH Messer- Platz 1 D - 65812 Bad Soden am Taunus Germany, 0049-(0)-6196 7760-200 DE - en 4/10



## Argon (refrigerated)

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: D-Ar-003B

PNEC (Predicted No-Effect Concentration) None available.

#### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available). Oxygen detectors should be used when asphyxiating gases may be released. Consider the use of a work permit system e.g. for maintenance activities.

#### 8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.

The following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected. Wear goggles and a face shield when transfilling or breaking transfer connections.

Standard EN 166 - Personal eye-protection - specifications.

Skin protection

· Eve/face protection

- Hand protection : Wear working gloves when handling gas containers.

Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.

Wear cold insulating gloves when transfilling or breaking transfer connections.

Standard EN 511 - Cold insulating gloves.

- Other Wear safety shoes while handling containers.

Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

· Respiratory protection Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be

used in oxygen-deficient atmospheres.

Self contained breathing apparatus is recommended, where unknown exposure may be

expected, e.g. during maintenance activities on installation systems.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

Consult respiratory device supplier's product information for the selection of the appropriate

device

· Thermal hazards None in addition to the above sections.

## 8.2.3. Environmental exposure controls

None necessary.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa : Gas - Colour : Colourless.

Odour : No odour warning properties.

Odour threshold is subjective and inadequate to warn of overexposure.

pΗ : Not applicable for gases and gas mixtures.

Melting point / Freezing point : -189 °C -189 °C -186 °C Boiling point

Not applicable for gases and gas mixtures. Flash point

Non flammable. Flammability Lower explosion limit Not available Upper explosion limit Not available Vapour pressure [20°C] Not applicable. Vapour pressure [50°C] Not applicable. Not applicable Density Not applicable. Vapour density

Relative density, liquid (water=1) 1.4 Relative density, gas (air=1) 1.38

Messer Industriegase GmbH Messer- Platz 1 D - 65812 Bad Soden am Taunus Germany, 0049-(0)-6196 7760-200

DE - en



## Argon (refrigerated)

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: D-Ar-003B

Water solubility : 67.3 mg/l

Partition coefficient n-octanol/water (Log Kow) : Not applicable for inorganic products.

Auto-ignition temperature : Non flammable.

Decomposition temperature : Not applicable.

Viscosity, kinematic : No reliable data available.

Particle characteristics : Not applicable for gases and gas mixtures.

#### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Explosive properties : Not applicable.

Oxidising properties : Not applicable.

Critical temperature [°C] : -122 °C

9.2.2. Other safety characteristics

Molar mass : 40 g/mol

Evaporation rate : Not applicable for gases and gas mixtures.

Gas group : Press. Gas (Ref. Liq.)

Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

ground level.

## SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Avoid moisture in installation systems.

10.5. Incompatible materials

For additional information on compatibility refer to ISO 11114.

Materials such as carbon steel, low alloy carbon steel and plastic become brittle at low temperatures and are subject to failure. Use appropriate materials compatible with the

cryogenic conditions present in refrigerated liquefied gas systems.

10.6. Hazardous decomposition products

None.

## **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Toxicological effects not expected from this product if occupational exposure limit values are

not exceeded.

Skin corrosion/irritation: No known effects from this product.Serious eye damage/irritation: No known effects from this product.Respiratory or skin sensitisation: No known effects from this product.Germ cell mutagenicity: No known effects from this product.Carcinogenicity: No known effects from this product.Toxic for reproduction : Fertility: No known effects from this product.Toxic for reproduction : unborn child: No known effects from this product.

Messer Industriegase GmbH Messer- Platz 1 D - 65812 Bad Soden am Taunus Germany, 0049-(0)-6196 7760-200 DE - en



## Argon (refrigerated)

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: D-Ar-003B

STOT-single exposure: No known effects from this product.STOT-repeated exposure: No known effects from this product.

Aspiration hazard : Not applicable for gases and gas mixtures.

11.2. Information on other hazards

Other information : The substance/mixture has no endocrine disrupting properties.

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Assessment : No ecological damage caused by this product.

EC50 48h - Daphnia magna [mg/l] : No data available. EC50 72h - Algae [mg/l] : No data available. LC50 96 h - Fish [mg/l] : No data available.

12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

12.3. Bioaccumulative potential

Assessment : No data available.

12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.

Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment

Assessment : No data available.

12.6. Endocrine disrupting properties

The substance/mixture has no endocrine disrupting properties.

12.7. Other adverse effects

Other adverse effects : Can cause frost damage to vegetation.

Effect on the ozone layer : None.

Effect on global warming : No known effects from this product.

None.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Do not discharge into any place where its accumulation could be dangerous.

May be vented to atmosphere in a well ventilated place. Return unused product in original container to supplier.

List of hazardous waste codes (from Commission

Decision 2000/532/EC as amended)

16 05 05: Gases in pressure containers other than those mentioned in 16 05 04.

#### 13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

## **SECTION 14: Transport information**

#### 14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN

UN-No. : 1951

Messer Industriegase GmbH Messer- Platz 1 D - 65812 Bad Soden am Taunus Germany, 0049-(0)-6196 7760-200 DE - en



## Argon (refrigerated)

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: D-Ar-003B

#### 14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : ARGON, REFRIGERATED LIQUID

Transport by air (ICAO-TI / IATA-DGR) : Argon, refrigerated liquid

Transport by sea (IMDG) : ARGON, REFRIGERATED LIQUID

14.3. Transport hazard class(es)

Labelling

2

Transport by road/rail (ADR/RID)

Class : 2
Classification code : 3A
Hazard identification number : 22

Tunnel Restriction : C/E - Tank carriage : Passage forbidden through tunnels of category C, D and E. Other

2.2 : Non flammable, non-toxic gases.

carriage: Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2
Emergency Schedule (EmS) - Fire : F-C
Emergency Schedule (EmS) - Spillage : S-V

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable
Transport by air (ICAO-TI / IATA-DGR) : Not applicable
Transport by sea (IMDG) : Not applicable

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.
Transport by air (ICAO-TI / IATA-DGR) : None.
Transport by sea (IMDG) : None.

#### 14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P203

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : 202.
Cargo Aircraft only : 202.
Transport by sea (IMDG) : P203

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's

compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in

the event of an accident or an emergency.

Before transporting product containers:

- Ensure there is adequate ventilation.

- Ensure that containers are firmly secured.
- Ensure valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

#### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

DE - en



## Argon (refrigerated)

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: D-Ar-003B

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU-Regulations** 

Restrictions on use : None.

Other information, restriction and prohibition

: Ensure all national/local regulations are observed.

regulations

Seveso Directive: 2012/18/EU (Seveso III) : Not covered.

**National regulations** 

Water hazard class (WGK) : nwg - Non-hazardous to water

Kenn-Nr. : 1348

Regulatory reference : National / local legislations :

Sec15 DE General.

Classification for storage according to TRGS 510: 2A Gase (ohne Aerosolpackungen und

Feuerzeuge).

15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

#### **SECTION 16: Other information**

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 2020/878.

Abbreviations and acronyms : ATE - Acute Toxicity Estimate

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

(EC) No 1907/2006

EINECS - European Inventory of Existing Commercial Chemical Substances

CAS# - Chemical Abstract Service number

LC50 - Lethal Concentration to 50 % of a test population

RMM - Risk Management Measures

PBT - Persistent, Bioaccumulative and Toxic vPvB - Very Persistent and Very Bioaccumulative

STOT- SE: Specific Target Organ Toxicity - Single Exposure

CSA - Chemical Safety Assessment

EN - European Standard UN - United Nations

ADR - European Agreement concerning the International Carriage of Dangerous Goods by

Road

IATA - International Air Transport Association

IMDG code - International Maritime Dangerous Goods

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

WGK - Water Hazard Class

STOT - RE : Specific Target Organ Toxicity - Repeated Exposure

PPE - Personal Protection Equipment

UFI : Unique Formula Identifier

Training advice : The hazard of asphyxiation is often overlooked and must be stressed during operator

training.

For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at

http://www.eiga.eu..

Further information : Classification in accordance with the procedures and calculation methods of Regulation

(EC) 1272/2008 (CLP).

Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at http://www.Eiga.eu .

Messer Industriegase GmbH Messer- Platz 1 D - 65812 Bad Soden am Taunus Germany, 0049-(0)-6196 7760-200 DE - en



# Argon (refrigerated)

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Reference number: D-Ar-003B

Full text of H- and EUH-statements		
H281	Contains refrigerated gas; may cause cryogenic burns or injury.	
Press. Gas (Ref. Liq.)	Gases under pressure : Refrigerated liquefied gas	

DISCLAIMER OF LIABILITY

 Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
 Details given in this document are believed to be correct at the time of going to press.
 Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**End of document**