

Safety Data Sheet

Butadiene 1,3

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SDS Reference Number: D-C4H6-013

Issue date: 1/7/2015 Revision date: 12/15/2025 Supersedes version of: 1/3/2023 Version: 0.5

Danger



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name	:	Butadiene 1,3
SDS no	:	D-C4H6-013
Other means of identification	:	Butadiene 1,3
	CAS-No.	: 106-99-0
	EC-No.	: 203-450-8
	EC Index-No.	: 601-013-00-X
REACH registration No	:	01-2119471988-16
Chemical formula	:	C4H6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	:	See the list of identified uses and exposure scenarios in the annex of the safety data sheet. Perform risk assessment prior to use.
Uses advised against	:	Consumer use. Uses other than those listed above are not supported, contact your supplier for more information on other uses. Attention: These products must not be applied to humans or animals unless they are expressly designated as medical or medicinal gases!.

1.3. Details of the supplier of the safety data sheet

Messer Industriegase GmbH
Messer- Platz 1
D - 65812 Bad Soden am Taunus
Germany
T +49 (0) 6196 7760-200, F +49 (0) 6196 7760-280
SDB.de@messergroup.com, www.messer.de

1.4. Emergency telephone number

Emergency telephone number	:	Messer Produktionsgesellschaft mbH Salzgitter, +49 (0) 5341 21-9333, erreichbar Montags 0:00 bis Sonntags 24:00
----------------------------	---	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards	Flammable gases, Category 1A	H220
	Gases under pressure : Liquefied gas	H280
Health hazards	Germ cell mutagenicity, Category 1B	H340
	Carcinogenicity, Category 1A	H350

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazard statements (CLP)

: H220 - Extremely flammable gas.
H280 - Contains gas under pressure; may explode if heated.
H340 - May cause genetic defects.
H350 - May cause cancer.

Precautionary statements (CLP)

- Prevention

: P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- Response

: P308+P313 - IF exposed or concerned: Get medical advice/attention.
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381 - In case of leakage, eliminate all ignition sources.

- Storage

: P403 - Store in a well-ventilated place.

Supplemental information

: Restricted to professional users.

2.3. Other hazards

Contact with liquid may cause cold burns/frostbite.
Not classified as PBT or vPvB.
The substance/mixture has no endocrine disrupting properties.
Not classified as PMT or vPvM.

SECTION 3: Composition/information on ingredients

3.1. Substances

Safety Data Sheet

Butadiene 1,3

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS Reference Number: D-C4H6-013

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP] ATE, EUH-statements, M-Factors
Butadiene 1,3	CAS-No.: 106-99-0 EC-No.: 203-450-8 EC Index-No.: 601-013-00-X REACH registration No: 01-2119471988-16	100	Flam. Gas 1A, H220 Press. Gas (Liq.), H280 Muta. 1B, H340 Carc. 1A, H350

Contains no other components or impurities which will influence the classification of the product.

3.2. Mixtures Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.
Dry powder.
Carbon dioxide.
Shutting off the source of the gas is the preferred method of control.
Be aware of the risk of formation of static electricity with the use of CO2 extinguishers. Do not use them in places where a flammable atmosphere may be present.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : Carbon monoxide.

5.3. Advice for firefighters

Specific methods	: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire. Move containers away from the fire area if this can be done without risk.
Special protective equipment for fire fighters	: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus. Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: Act in accordance with local emergency plan. Try to stop release. Evacuate area. Eliminate ignition sources. Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Stay upwind. See section 8 of the SDS for more information on personal protective equipment.
For emergency responders	: Monitor concentration of released product. Consider the risk of potentially explosive atmospheres. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. See section 5.3 of the SDS for more information.

6.2. Environmental precautions

Try to stop release.

6.3. Methods and material for containment and cleaning up

Ventilate area.

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product

- : Take precautionary measures against static discharge.
- Keep away from ignition sources (including static discharges).
- Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
- Purge air from system before introducing gas.
- Avoid exposure, obtain special instructions before use.
- Do not smoke while handling product.
- Avoid suck back of water, acid and alkalis.
- Only experienced and properly instructed persons should handle gases under pressure.
- Ensure the complete gas system was (or is regularly) checked for leaks before use.
- Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment.
- Consider the use of only non-sparking tools.
- The product must be handled in accordance with good industrial hygiene and safety procedures.
- Consider pressure relief device(s) in gas installations.
- Do not breathe gas.
- Avoid release of product into work area.
- Ensure equipment is adequately earthed.

Safe handling of the gas receptacle

- : Do not allow backfeed into the container.
- Protect containers from physical damage; do not drag, roll, slide or drop.
- When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
- Leave valve protection caps, when provided, in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
- If user experiences any difficulty operating valve discontinue use and contact supplier.
- Never attempt to repair or modify container valves or safety relief devices.
- Damaged valves should be reported immediately to the supplier.
- Keep container valve outlets clean and free from contaminants particularly oil and water.
- Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
- Close container valve after each use and when empty, even if still connected to equipment.
- Never attempt to transfer gases from one cylinder/container to another.
- Never use direct flame or electrical heating devices to raise the pressure of a container.
- Do not remove or deface labels provided by the supplier for the identification of the content of the container.
- Suck back of water into the container must be prevented.
- Open valve slowly to avoid pressure shock.

Safety Data Sheet

Butadiene 1,3

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS Reference Number: D-C4H6-013

7.2. Conditions for safe storage, including any incompatibilities

Store locked up.
Segregate from oxidant gases and other oxidants in store.
All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere.
Observe all regulations and local requirements regarding storage of containers.
Containers should not be stored in conditions likely to encourage corrosion.
Container valve guards or caps, when provided, should be in place.
Containers should be stored in the vertical position and properly secured to prevent them from falling over.
Stored containers should be periodically checked for general condition and leakage.
Keep container below 50°C in a well ventilated place.
Store containers in location free from fire risk and away from sources of heat and ignition.
Keep away from combustible materials.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Butadiene 1,3 (106-99-0)	
Germany - Occupational Exposure Limits (TRGS 910)	
Local name	1,3-Butadien
Acceptable concentration (Volume conc.)	0.2 ppm
Acceptable concentration (Weight conc.)	0.5 mg/m ³
Notes	b) Akzeptanzkonzentration assoziiert mit Risiko 4:10000
Tolerance concentration (Volume conc.)	2 ppm
Tolerance concentration (Weight conc.)	5 mg/m ³
Tolerance concentration excess factor	8
Equivalence value for acceptable concentration	600 µg/g creatinine 10 µg/g creatinine
Equivalence value for tolerance concentration	2900 µg/g creatinine 80 µg/g creatinine
Parameter	3,4- Dihydroxybutyl-merkaptursäure (DHBMA) 2-Hydroxy-3-butenyl-merkaptursäure (MHBMA)
Testing material	U - Urin
Testing time	b - Expositionsende bzw. Schichtende, c - Bei Langzeitexposition: am Schichtende nach mehreren vorangegangenen Schichten

Safety Data Sheet

Butadiene 1,3

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS Reference Number: D-C4H6-013

Regulatory reference	TRGS 910
Butadiene 1,3 (106-99-0)	
DNEL: Derived no effect level (Workers)	
Long-term - systemic effects, inhalation	2.21 mg/m ³

PNEC (Predicted No-Effect Concentration) : None established.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Product to be handled in a closed system and under strictly controlled conditions.
Provide adequate general and local exhaust ventilation.
Preferably use permanent leak-tight installations (e.g. welded pipes).
Systems under pressure should be regularly checked for leakages.
Ensure exposure is below occupational exposure limits (where available).
Gas detectors should be used when flammable gases/vapours may be released.
Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

• Eye/face protection

: Wear goggles when transfilling or breaking transfer connections.
Standard EN 166 - Personal eye-protection - specifications.
Standard EN ISO 16321-1 - Eye and face protection for occupational use Part 1: General requirements.

• Skin protection

- Hand protection

: Wear working gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher. Recommended types include wrist gloves from leather or synthetic material with equivalent performance, fabric gloves, fabric gloves with leather palms.
Permeation time: minimum >30min short term exposure: material / thickness [mm] Butyl rubber (IIR) 0,7.
Permeation time: minimum >480min long term exposure: material / thickness [mm] Fluoroelastomer (FKM) 0,4.

Wear cold insulating gloves when transfilling or breaking transfer connections.

Standard EN 511 - Cold insulating gloves, performance level 1 or higher. Recommended types include insulated gauntlets or gloves specifically selected to prevent liquid penetration and ingress of cryogenic liquids and to provide mechanical resistance.

- Other

: Consider the use of flame resistant anti-static safety clothing.
Standard EN ISO 14116 - Limited flame spread materials.
Standard EN 1149-5 - Protective clothing: Electrostatic properties.
Wear safety shoes while handling containers.
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

Safety Data Sheet

Butadiene 1,3

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS Reference Number: D-C4H6-013

- Respiratory protection : Recommended: Filter AX (brown).
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.
Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.
Gas filters do not protect against oxygen deficiency.
Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks .
Keep self contained breathing apparatus readily available for emergency use.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
- Thermal hazards : None in addition to the above sections.

8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa : Gas.
- Colour : Colourless.

Odour : Mildly aromatic. Poor warning properties at low concentrations.

Melting point / Freezing point : -109 °C

Boiling point : -4.5 °C

Flammability : Extremely flammable gas.

Lower explosion limit : 1.4 vol %

Upper explosion limit : 16.3 vol %

Flash point : Not applicable for gases and gas mixtures.

Auto-ignition temperature : 415 °C

Decomposition temperature : Not applicable.

pH : Not applicable for gases and gas mixtures.

Viscosity, kinematic : No reliable data available.

Water solubility [20°C] : 1025 mg/l

Partition coefficient n-octanol/water (Log Kow) : 1.99

Vapour pressure [20°C] : 2.4 bar(a)

Vapour pressure [50°C] : 5.7 bar(a)

Density and/or relative density : Not applicable for gases and gas mixtures.

Relative vapour density (air=1) : 1.9

Particle characteristics : Not applicable for gases and gas mixtures.

Nanoforms are not relevant for gases and gas mixtures.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Oxidising properties : No oxidising properties.
Critical temperature [°C] : 152 °C

9.2.2. Other safety characteristics

Molar mass : 54 g/mol
Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.
May polymerise.
Inhibitor usually added.

10.3. Possibility of hazardous reactions

Can form explosive mixture with air.
May react violently with oxidants.

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Avoid moisture in installation systems.

10.5. Incompatible materials

Air, Oxidisers.
For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Toxicological effects not expected by inhalation from this product if occupational exposure limit values are not exceeded.
Skin corrosion/irritation : No known effects from this product.
Serious eye damage/irritation : No known effects from this product.
Respiratory or skin sensitisation : No known effects from this product.
Germ cell mutagenicity : May cause genetic defects.
Carcinogenicity : May cause cancer.

Toxic for reproduction : Fertility : No known effects from this product.
Toxic for reproduction : unborn child : No known effects from this product.
STOT-single exposure : No known effects from this product.
STOT-repeated exposure : No known effects from this product.
Aspiration hazard : Not applicable for gases and gas mixtures.

11.2. Information on other hazards

Other information : The substance/mixture has no endocrine disrupting properties.

SECTION 12: Ecological information

12.1. Toxicity

Assessment : Classification criteria are not met.
EC50 48h - Daphnia magna [mg/l] : 24 mg/l
EC50 72h - Algae [mg/l] : 11 mg/l
LC50 96 h - Fish [mg/l] : 43 mg/l

12.2. Persistence and degradability

Assessment : Not readily biodegradable.

12.3. Bioaccumulative potential

Assessment : Not expected to bioaccumulate due to the low log Kow (log Kow < 4).
See section 9.

12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.
Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

12.6. Endocrine disrupting properties

Assessment : The substance/mixture has no endocrine disrupting properties.

12.7. Other adverse effects

Other adverse effects : Not classified as PMT or vPvM.
Effect on the ozone layer : No effect on the ozone layer.
Effect on global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Contact supplier if guidance is required.
Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor.
Ensure that the emission levels from local regulations or operating permits are not exceeded.
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.eu> for more guidance on suitable disposal methods.
Must not be discharged to atmosphere.
Return unused product in original container to supplier.
: 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN
UN-No. : 1010

14.2. UN proper shipping name

Transport by road/rail/inland waterways (ADR/RID/ADN) : BUTADIENES, STABILIZED
Transport by air (ICAO-TI / IATA-DGR) : Butadienes, stabilized
Transport by sea (IMDG) : BUTADIENES, STABILIZED

14.3. Transport hazard class(es)

Labelling



2.1 : Flammable gases.

Transport by road/rail/inland waterways (ADR/RID/ADN)

Class : 2
Classification code : 2F
Hazard identification number : 239
Tunnel Restriction : B/D - Tank carriage: Passage forbidden through tunnels of category B, C, D and E. Other carriage: Passage forbidden through tunnels of category D and E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.1

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.1

Emergency Schedule (EmS) - Fire : F-D

Emergency Schedule (EmS) - Spillage : S-U

14.4. Packing group

Transport by road/rail/inland waterways : Not applicable.

(ADR/RID/ADN)

Transport by air (ICAO-TI / IATA-DGR) : Not applicable.

Transport by sea (IMDG) : Not applicable.

14.5. Environmental hazards

Transport by road/rail/inland waterways : None.

(ADR/RID/ADN)

Transport by air (ICAO-TI / IATA-DGR) : None.

Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail/inland waterways : P200.

(ADR/RID/ADN)

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : Forbidden.

Cargo Aircraft only : 200.

Transport by sea (IMDG) : P200.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
Before transporting product containers:
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use : Restricted to professional users (Annex XVII REACH).

Other information, restriction and prohibition : None.

regulations Not listed on the PIC list (Regulation EU 649/2012).

Not listed on the POP list (Regulation EU 2019/1021).

Seveso Directive : 2012/18/EU (Seveso III) : Covered.

Safety Data Sheet

Butadiene 1,3

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS Reference Number: D-C4H6-013

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P2 FLAMMABLE GASES Flammable gases, Category 1 or 2	10	50

National regulations

Water hazard class (WGK) : 2 - Significantly hazardous to water.

Kenn-Nr. : 218

Regulatory reference : Law on the Protection of Young People at Work (Jugendarbeitsschutzgesetz-JArbSchG)
Ordinance on Industrial Safety and Health (BetrSichV)
TRBS 3145/TRGS 745 - Transportable pressurized gas containers - Filling, holding, internal transport, emptying
TRGS 510 - Storage of hazardous substances in transportable containers
TRGS 407 - Activities with gases - Risk assessment
TRBS 2141 - Hazards due to steam and pressure - General requirements
The Ordinance on Installations for the Handling of Substances Hazardous to Water (AwSV)
Storage class according to TRGS 510: 2A Gases (without aerosol dispensers and lighters)
Technical Instructions on Air Quality Control (TA Luft).
TRGS 725 - Gefährliche explosionsfähige Atmosphäre -Mess-, Steuer- und Regeleinrichtungen im Rahmen von Explosionsschutzmaßnahmen.
Gesetz zum Schutz von Müttern bei der Arbeit, in der Ausbildung und im Studium (Mutterschutzgesetz – MuSchG)
Verordnung über Verbote und Beschränkungen des Inverkehrbringens gefährlicher Stoffe, Zubereitungen und Erzeugnisse nach dem Chemikaliengesetz (Chemikalien-Verbotsverordnung-ChemVerbotsV).

15.2. Chemical safety assessment

A CSA has been carried out.

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 2020/878.

Safety Data Sheet

Butadiene 1,3

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS Reference Number: D-C4H6-013

Abbreviations and acronyms

- : ATE - Acute Toxicity Estimate.
- CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.
- REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
- EINECS - European Inventory of Existing Commercial Chemical Substances.
- CAS# - Chemical Abstract Service number.
- PPE - Personal Protection Equipment.
- LC50 - Lethal Concentration to 50 % of a test population.
- RMM - Risk Management Measures.
- PBT - Persistent, Bioaccumulative and Toxic.
- vPvB - Very Persistent and Very Bioaccumulative.
- STOT- SE : Specific Target Organ Toxicity - Single Exposure.
- CSA - Chemical Safety Assessment.
- EN - European Standard.
- UN - United Nations.
- ADR - Agreement concerning the International Carriage of Dangerous Goods by Road.
- IATA - International Air Transport Association.
- IMDG code - International Maritime Dangerous Goods.
- RID - Regulations concerning the International Carriage of Dangerous Goods by Rail.
- WGK - Water Hazard Class.
- STOT - RE : Specific Target Organ Toxicity - Repeated Exposure.
- UFI : Unique Formula Identifier.
- ADN -International Carriage of Dangerous Goods by Inland Waterways.
- PROC -Process category.
- ERC – Environmental release category.
- PMT - Persistent, Mobile and Toxic.
- vPvM – very Persistent and very Mobile.

Training advice

: Ensure operators understand the flammability hazard.

Further information

: Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).
Key literature references and sources of data are maintained in EIGA Doc 169 : 'Classification and Labelling Guide', downloadable at <http://www.Eiga.eu> .

Full text of H- and EUH-statements	
Carc. 1A	Carcinogenicity, Category 1A
Flam. Gas 1A	Flammable gases, Category 1A
Muta. 1B	Germ cell mutagenicity, Category 1B
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H340	May cause genetic defects.
H350	May cause cancer.

Safety Data Sheet

Butadiene 1,3

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
 SDS Reference Number: D-C4H6-013

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
 Details given in this document are believed to be correct at the time of going to press.
 Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Annex to the safety data sheet

Table of contents of the Annex

Identified Uses	Es N°	Short title	ERC	PROC	Page
Transfilling in pressure receptacles	EIGA013-1	Industrial uses, closed contained conditions	ERC2	PROC1 PROC8b PROC9	16
Formulation of mixtures in pressure receptacles	EIGA013-1	Industrial uses, closed contained conditions	ERC2	PROC1 PROC8b PROC9	16
Calibration of analysis equipment	EIGA013-1	Industrial uses, closed contained conditions	ERC8d	PROC1	16
Feedstock in chemical processes	EIGA013-1	Industrial uses, closed contained conditions	ERC6a	PROC2 PROC3 PROC4	16

Exposure scenario

Butadiene 1,3

Annex to the safety data sheet

Reference number: D-C4H6-013

CAS-No.: 106-99-0 Product form: Substance Physical state: Gas

1. EIGA013-1: Industrial uses, closed contained conditions

1.1. Title section

Industrial uses, closed contained conditions

ES Ref.: EIGA013-1

Revision date: 10/1/2016

Processes, tasks, activities covered	Industrial uses, including product transfers and associated laboratory activities within different closed or contained systems
--------------------------------------	--

Environment	Use descriptors
CS1	ERC2

Worker	Use descriptors
CS2	PROC1
CS3	PROC2, PROC3, PROC4
CS4	PROC8b, PROC9

Assessment method	ECETOC TRA 2.0
-------------------	----------------

1.2. Conditions of use affecting exposure

1.2.1. Control of environmental exposure: ERC2

ERC2	Formulation into mixture
------	--------------------------

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used, frequency and duration of use (or from service life)	
The actual tonnage handled per site is not considered to influence the immissions as such for this scenario as there is practically no release	

Exposure scenario

Butadiene 1,3

Annex to the safety data sheet

Reference number: D-C4H6-013

CAS-No.: 106-99-0 Product form: Substance Physical state: Gas

Technical and organisational conditions and measures	
Wastewater emission controls are not applicable as there is no direct release to wastewater	
Soil emission controls are not applicable as there is no direct release to soil	
Ensure operatives are trained to minimise releases	

Conditions and measures related to sewage treatment plant	
Not applicable as there is no release to wastewater	

Conditions and measures related to treatment of waste (including article waste)	
See section 13 of the SDS	

Other conditions affecting environmental exposure	
No additional information	

1.2.2. Control of worker exposure: PROC1

PROC1	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
-------	--

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures	
Handle product within a closed system	

Exposure scenario

Butadiene 1,3

Annex to the safety data sheet

Reference number: D-C4H6-013

CAS-No.: 106-99-0 Product form: Substance Physical state: Gas

Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
See section 8 of the SDS.	

Other conditions affecting workers exposure	
Indoor or outdoor use	

1.2.3. Control of worker exposure: PROC2, PROC3, PROC4

PROC2	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC3	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC4	Chemical production where opportunity for exposure arises

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 1 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures	
Handle product within a closed system	

Exposure scenario

Butadiene 1,3

Annex to the safety data sheet

Reference number: D-C4H6-013

CAS-No.: 106-99-0 Product form: Substance Physical state: Gas

During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Ensure samples are obtained under containment or extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection measures have to be applied in case of potential exposure only.	
See section 8 of the SDS.	

Other conditions affecting workers exposure	
Indoor or outdoor use	

1.2.4. Control of worker exposure: PROC8b, PROC9

PROC8b	Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC9	Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 4 h/day
Covers frequency up to:	5 days/week

Exposure scenario

Butadiene 1,3

Annex to the safety data sheet

Reference number: D-C4H6-013

CAS-No.: 106-99-0 Product form: Substance Physical state: Gas

Technical and organisational conditions and measures	
Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Ensure samples are obtained under containment or extract ventilation.	
Fill containers at dedicated fill points supplied with local extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection measures have to be applied in case of potential exposure only.	
See section 8 of the SDS.	

Other conditions affecting workers exposure	
Indoor or outdoor use	

1.3. Exposure estimation and reference to its source

1.3.1. Environmental release and exposure: ERC2

The exposure of aquatic, terrestrial, sediment and sewage treatment microorganisms is considered to be negligible because the substance partitions primarily to air when released to the environment. Emission of the substance to the air compartment is regulated. The limits in place would also limit exposure to ecological receptors. Hence the risks are considered to be controlled for ecological receptors.

1.3.2. Worker exposure: PROC1

When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposure of workers and indirect human exposure via the environment is not expected to exceed the predicted DNELs and the resulting risk characterisation ratios are expected to be less than 1.

1.3.3. Worker exposure: PROC2, PROC3, PROC4

When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposure of workers and indirect human exposure via the environment is not expected to exceed the predicted DNELs and the resulting risk characterisation ratios are expected to be less than 1.

Exposure scenario

Butadiene 1,3

Annex to the safety data sheet

Reference number: D-C4H6-013

CAS-No.: 106-99-0 Product form: Substance Physical state: Gas

1.3.4. Worker exposure: PROC8b, PROC9

When the recommended risk management measures (RMMs) and operational conditions (OCs) are observed, exposure of workers and indirect human exposure via the environment is not expected to exceed the predicted DNELs and the resulting risk characterisation ratios are expected to be less than 1.

1.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

1.4.1. Environment

Guidance - Environment	Check that RMMs and OCs are as described above or of equivalent efficiency
------------------------	--

1.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : http://www.ecetoc.org/tra
-------------------	---

End of document