

# Safety Data Sheet

## Nitrous oxide (refrigerated)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SDS Reference Number: D-N2O-093B

Issue date: 4/1/2015 Revision date: 12/4/2025 Supersedes version of: 8/21/2023 Version: 4.5

### Danger



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name	: Nitrous oxide (refrigerated), Gourmet L
SDS no	: D-N2O-093B
Other means of identification	: Nitrous oxide (refrigerated)
	CAS-No. : 10024-97-2
	EC-No. : 233-032-0
	EC Index-No. : ---
REACH registration No	: 01-2119970538-25
Chemical formula	: N2O

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	: Industrial and professional uses. Perform risk assessment prior to use. See the list of identified uses and exposure scenarios in the annex of the safety data sheet. Food applications.
Uses advised against	: Consumer use. Do not inhale product on purpose because of the risk of asphyxiation. Do not inhale product on purpose because of the risk of narcotic effects. Uses other than those listed above are not supported, contact your supplier for more information on other uses.

### 1.3. Details of the supplier of the safety data sheet

Messer Industriegase GmbH  
Messer- Platz 1  
D - 65812 Bad Soden am Taunus  
Germany  
T +49 (0) 6196 7760-200, F +49 (0) 6196 7760-280  
[SDB.de@messergroup.com](mailto:SDB.de@messergroup.com), [www.messer.de](http://www.messer.de)

### 1.4. Emergency telephone number

Emergency telephone number	: Messer Produktionsgesellschaft mbH Salzgitter, +49 (0) 5341 21-9333, erreichbar Montags 0:00 bis Sonntags 24:00
----------------------------	---

# Safety Data Sheet

## Nitrous oxide (refrigerated)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
 SDS Reference Number: D-N2O-093B

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards	Oxidising Gases, Category 1	H270
	Gases under pressure : Refrigerated liquefied gas	H281
Health hazards	Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazard statements (CLP)

: H270 - May cause or intensify fire; oxidiser.  
 H281 - Contains refrigerated gas; may cause cryogenic burns or injury.  
 H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP)

- Prevention

: P260 - Do not breathe gas, vapours.  
 P244 - Keep valves and fittings free from oil and grease.  
 P220 - Keep away from clothing and other combustible materials.  
 P282 - Wear cold insulating gloves and either face shield or eye protection.  
 P304+P340+P315 - IF INHALED : Remove person to fresh air and keep comfortable for breathing.  
 Get immediate medical advice.  
 P336+P315 - Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.  
 P370+P376 - In case of fire: Stop leak if safe to do so.

- Response

: P304+P340+P315 - IF INHALED : Remove person to fresh air and keep comfortable for breathing.  
 Get immediate medical advice.  
 P336+P315 - Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.  
 P370+P376 - In case of fire: Stop leak if safe to do so.

- Storage

: P403 - Store in a well-ventilated place.

Supplemental information

: Do not inhale product on purpose because of the risk of asphyxiation.  
 Do not inhale product on purpose because of the risk of narcotic effects.

#### 2.3. Other hazards

Not classified as PBT or vPvB.  
 The substance/mixture has no endocrine disrupting properties.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

# Safety Data Sheet

## Nitrous oxide (refrigerated)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
SDS Reference Number: D-N2O-093B

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP] ATE, EUH-statements, M-Factors
Nitrous oxide (refrigerated)	CAS-No.: 10024-97-2 EC-No.: 233-032-0 EC Index-No.: --- REACH registration No: 01-2119970538-25	100	Ox. Gas 1, H270 Press. Gas (Ref. Liq.), H281 STOT SE 3, H336

Contains no other components or impurities which will influence the classification of the product.

**3.2. Mixtures** Not applicable

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

#### 4.2. Most important symptoms and effects, both acute and delayed

In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination.  
See section 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.  
Product does not burn, use fire control measures appropriate for the surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

- Specific hazards : Supports combustion.  
Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : Nitric oxide/nitrogen dioxide.

# Safety Data Sheet

## Nitrous oxide (refrigerated)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
SDS Reference Number: D-N2O-093B

### 5.3. Advice for firefighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.  
If possible, stop flow of product.  
Use water spray or fog to knock down fire fumes if possible.  
If leaking do not spray water onto container. Water surrounding area (from protected position) to contain fire.  
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus.  
Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams.  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel : Act in accordance with local emergency plan.  
Try to stop release.  
Evacuate area.  
Eliminate ignition sources.  
Ensure adequate air ventilation.  
Use protective clothing.  
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.  
Stay upwind.  
See section 8 of the SDS for more information on personal protective equipment.
- For emergency responders : Monitor concentration of released product.  
Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.  
See section 5.3 of the SDS for more information.

### 6.2. Environmental precautions

- Try to stop release.  
Liquid spillages can cause embrittlement of structural materials.

### 6.3. Methods and material for containment and cleaning up

- Ventilate area.

### 6.4. Reference to other sections

- See also sections 8 and 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Safe use of the product

- : Use no oil or grease.
- Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
- Do not smoke while handling product.
- Keep equipment free from oil and grease. For more guidance, refer to the EIGA Doc. 33 - Cleaning of Equipment for Oxygen Service downloadable at <http://www.eiga.eu>.
- Avoid suck back of water, acid and alkalis.
- Only experienced and properly instructed persons should handle gases under pressure.
- Ensure the complete gas system was (or is regularly) checked for leaks before use.
- The product must be handled in accordance with good industrial hygiene and safety procedures.
- Consider pressure relief device(s) in gas installations.
- For more guidance on safe use, refer to the EIGA Doc.176 "Safe practices for storage and handling of Nitrous oxide", downloadable at <http://www.eiga.org> and consult your supplier.
- Do not breathe gas.
- Avoid release of product into work area.
- Temperatures above 150°C (300°F) shall be avoided by all practical means, to reduce the likelihood of an explosive decomposition of the nitrous oxide.
- Clean all surfaces in direct contact with nitrous oxide as for oxygen service.
- Nitrous oxide transfer pumps shall be provided with an interlock to prevent dry running.
- Use self-limiting heating devices. Direct contact electric immersion heaters are not allowed.
- Use only lubricants and sealings approved for the specific gas service.

Safe handling of the gas receptacle

- : Refer to supplier's container handling instructions.
- Do not allow backfeed into the container.
- Protect containers from physical damage; do not drag, roll, slide or drop.
- When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
- Leave valve protection caps, when provided, in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
- If user experiences any difficulty operating valve discontinue use and contact supplier.
- Never attempt to repair or modify container valves or safety relief devices.
- Damaged valves should be reported immediately to the supplier.
- Keep container valve outlets clean and free from contaminants particularly oil and water.
- Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
- Close container valve after each use and when empty, even if still connected to equipment.
- Never attempt to transfer gases from one cylinder/container to another.
- Never use direct flame or electrical heating devices to raise the pressure of a container.
- Do not remove or deface labels provided by the supplier for the identification of the content of the container.
- Suck back of water into the container must be prevented.
- Open valve slowly to avoid pressure shock.

# Safety Data Sheet

## Nitrous oxide (refrigerated)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
SDS Reference Number: D-N2O-093B

### 7.2. Conditions for safe storage, including any incompatibilities

Segregate from flammable gases and other flammable materials in store.  
Observe all regulations and local requirements regarding storage of containers.  
Containers should not be stored in conditions likely to encourage corrosion.  
Container valve guards or caps, when provided, should be in place.  
Containers should be stored in the vertical position and properly secured to prevent them from falling over.  
Stored containers should be periodically checked for general condition and leakage.  
Keep container below 50°C in a well ventilated place.  
Store containers in location free from fire risk and away from sources of heat and ignition.  
Keep away from combustible materials.

### 7.3. Specific end use(s)

None.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Nitrous oxide (refrigerated) (10024-97-2)	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Distickstoffoxid
AGW (OEL TWA)	180 mg/m <sup>3</sup>
	100 ppm
Peak exposure limitation factor	2(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900

Nitrous oxide (refrigerated) (10024-97-2)	
DNEL: Derived no effect level (Workers)	
Long-term - systemic effects, inhalation	183 mg/m <sup>3</sup>

PNEC (Predicted No-Effect Concentration) : None established.

# Safety Data Sheet

## Nitrous oxide (refrigerated)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
SDS Reference Number: D-N2O-093B

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.  
Product to be handled in a closed system.  
Systems under pressure should be regularly checked for leakages.  
Ensure exposure is below occupational exposure limits (where available).  
Gas detectors should be used when oxidising gases may be released.  
Consider the use of a work permit system e.g. for maintenance activities.

#### 8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

##### • Eye/face protection

: Wear goggles and a face shield when transfilling or breaking transfer connections.  
Standard EN 166 - Personal eye-protection - specifications.  
Standard EN ISO 16321-1 - Eye and face protection for occupational use Part 1: General requirements.

##### • Skin protection

###### - Hand protection

: Wear working gloves when handling gas containers.  
Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher. Recommended types include wrist gloves from leather or synthetic material with equivalent performance, fabric gloves, fabric gloves with leather palms.  
Wear cold insulating gloves when transfilling or breaking transfer connections.  
Standard EN 511 - Cold insulating gloves, performance level 1 or higher. Recommended types include insulated gauntlets or gloves specifically selected to prevent liquid penetration and ingress of cryogenic liquids and to provide mechanical resistance.

###### - Other

: Consider the use of flame resistant safety clothing.  
Standard EN ISO 14116 - Limited flame spread materials.  
Wear safety shoes while handling containers.  
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

##### • Respiratory protection

: Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.  
Keep self contained breathing apparatus readily available for emergency use.  
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.  
Consult respiratory device supplier's product information for the selection of the appropriate device.

##### • Thermal hazards

: None in addition to the above sections.

#### 8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

##### Appearance

- Physical state at 20°C / 101.3kPa : Gas.
- Colour : Colourless liquid.

Odour : Sweetish. Poor warning properties at high concentrations.

Melting point / Freezing point : -90.81 °C

Boiling point : -88.5 °C

Flammability : Non flammable.

Lower explosion limit : Not applicable.

Upper explosion limit : Not applicable.

Flash point : Not applicable for gases and gas mixtures.

Auto-ignition temperature : Non flammable.

Decomposition temperature : Not applicable.

pH : Not applicable for gases and gas mixtures.

Viscosity, kinematic : No reliable data available.

Water solubility [20°C] : 1500 mg/l

Partition coefficient n-octanol/water (Log Kow) : 0.4

Vapour pressure [20°C] : 50.8 bar(a)

Vapour pressure [50°C] : Not applicable.

Density and/or relative density : Not applicable for gases and gas mixtures.

Relative vapour density (air=1) : 1.5

Particle characteristics : Not applicable for gases and gas mixtures.  
Nanoforms are not relevant for gases and gas mixtures.

#### 9.2. Other information

##### 9.2.1. Information with regard to physical hazard classes

Oxidising properties : Oxidiser.

- Coefficient of oxygen equivalency (Ci) : 0.6

Critical temperature [°C] : 36.4 °C

##### 9.2.2. Other safety characteristics

Molar mass : 44 g/mol

Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

# Safety Data Sheet

## Nitrous oxide (refrigerated)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
 SDS Reference Number: D-N2O-093B

### 10.2. Chemical stability

At temperatures over 575°C and at atmospheric pressure, nitrous oxide decomposes into nitrogen and oxygen.

In the presence of catalysts (e.g. halogen products, mercury, nickel, platinum) the rate of decomposition increases and decomposition can occur at even lower temperatures.

Nitrous oxide dissociation is irreversible and exothermic, leading to a considerable rise in pressure.

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

May react violently with reducing agents.

Violently oxidises organic material.

### 10.4. Conditions to avoid

Avoid moisture in installation systems.

### 10.5. Incompatible materials

May react violently with combustible materials.

May react violently with reducing agents.

Keep equipment free from oil and grease. For more guidance, refer to the EIGA Doc. 33 - Cleaning of Equipment for Oxygen Service downloadable at <http://www.eiga.eu>.

For additional information on compatibility refer to ISO 11114.

Materials such as carbon steel, low alloy carbon steel and plastic become brittle at low temperatures and are subject to failure. Use appropriate materials compatible with the cryogenic conditions present in refrigerated liquefied gas systems.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity** : No additional information available

#### Nitrous oxide (refrigerated) (10024-97-2)

LC50 Inhalation - Rat [ppm]	500000 ppm/4h
-----------------------------	---------------

**Skin corrosion/irritation** : No known effects from this product.

**Serious eye damage/irritation** : No known effects from this product.

**Respiratory or skin sensitisation** : No known effects from this product.

**Germ cell mutagenicity** : No known effects from this product.

**Carcinogenicity** : No known effects from this product.

**Toxic for reproduction : Fertility** : No known effects from this product.

**Toxic for reproduction : unborn child** : No known effects from this product.

**STOT-single exposure** : May cause drowsiness or dizziness.

# Safety Data Sheet

## Nitrous oxide (refrigerated)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
SDS Reference Number: D-N2O-093B

<b>STOT-repeated exposure</b>	: Hemotoxic effect. Neurologic effect. At low concentrations:
<b>Target organ(s)</b>	: Central nervous system. Erythrocytes. Kidneys. liver.
<b>Aspiration hazard</b>	: Not applicable for gases and gas mixtures.

### **11.2. Information on other hazards**

Other information	: Inhalation causes narcotic effects. The substance/mixture has no endocrine disrupting properties.
-------------------	--

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

Assessment	: No ecological damage caused by this product.
EC50 48h - Daphnia magna [mg/l]	: No data available.
EC50 72h - Algae [mg/l]	: No data available.
LC50 96 h - Fish [mg/l]	: No data available.

### **12.2. Persistence and degradability**

Assessment	: Not applicable for inorganic products. Study scientifically unjustified.
------------	--

### **12.3. Bioaccumulative potential**

No additional information available

### **12.4. Mobility in soil**

Assessment	: Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.
------------	---

### **12.5. Results of PBT and vPvB assessment**

Assessment	: Not classified as PBT or vPvB.
------------	----------------------------------

### **12.6. Endocrine disrupting properties**

Assessment	: The substance/mixture has no endocrine disrupting properties.
------------	---

### **12.7. Other adverse effects**

Other adverse effects	: Can cause frost damage to vegetation.
Effect on the ozone layer	: No effect on the ozone layer.
Global warming potential [CO <sub>2</sub> =1]	: 298
Effect on global warming	: When discharged in large quantities may contribute to the greenhouse effect. Contains greenhouse gas(es).

# Safety Data Sheet

## Nitrous oxide (refrigerated)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
 SDS Reference Number: D-N2O-093B

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Discharge to atmosphere in large quantities should be avoided.  
 Contact supplier if guidance is required.  
 Ensure that the emission levels from local regulations or operating permits are not exceeded.  
 Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.eu> for more guidance on suitable disposal methods.  
 Do not discharge into any place where its accumulation could be dangerous.  
 May be vented to atmosphere in a well ventilated place.  
 Return unused product in original container to supplier.  
 : 16 05 04 \*: Gases in pressure containers (including halons) containing hazardous substances.

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)

#### 13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

### SECTION 14: Transport information

#### 14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN  
 UN-No. : 2201

#### 14.2. UN proper shipping name

**Transport by road/rail/inland waterways (ADR/RID/ADN)** : NITROUS OXIDE, REFRIGERATED LIQUID  
**Transport by air (ICAO-TI / IATA-DGR)** : Nitrous oxide, refrigerated liquid  
**Transport by sea (IMDG)** : NITROUS OXIDE, REFRIGERATED LIQUID

#### 14.3. Transport hazard class(es)

Labelling :



2.2 : Non flammable, non-toxic gases.  
 5.1 : Oxidizing substances.

#### Transport by road/rail/inland waterways (ADR/RID/ADN)

Class : 2  
 Classification code : 30  
 Hazard identification number : 225  
 Tunnel Restriction : C/E - Tank carriage : Passage forbidden through tunnels of category C, D and E. Other carriage : Passage forbidden through tunnels of category E

#### Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2 (5.1)  
 Emergency Schedule (EmS) - Fire : F-C

Emergency Schedule (EmS) - Spillage : S-W

#### **14.4. Packing group**

Transport by road/rail/inland waterways : Not applicable.

(ADR/RID/ADN)

Transport by air (ICAO-TI / IATA-DGR) : Not applicable.

Transport by sea (IMDG) : Not applicable.

#### **14.5. Environmental hazards**

Transport by road/rail/inland waterways : None.

(ADR/RID/ADN)

Transport by air (ICAO-TI / IATA-DGR) : None.

Transport by sea (IMDG) : None.

#### **14.6. Special precautions for user**

##### **Packing Instruction(s)**

Transport by road/rail/inland waterways : P203.

(ADR/RID/ADN)

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : Forbidden.

Cargo Aircraft only : Forbidden.

Transport by sea (IMDG) : P203.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.  
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.  
Before transporting product containers:  
- Ensure there is adequate ventilation.  
- Ensure that containers are firmly secured.  
- Ensure valve is closed and not leaking.  
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.  
- Ensure valve protection device (where provided) is correctly fitted.

#### **14.7. Maritime transport in bulk according to IMO instruments**

Not applicable.

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### **EU-Regulations**

Restrictions on use : None.

Other information, restriction and prohibition : Not listed on the PIC list (Regulation EU 649/2012).

regulations : Not listed on the POP list (Regulation EU 2019/1021).

Seveso Directive : 2012/18/EU (Seveso III) : Covered.

#### **National regulations**

Water hazard class (WGK) : 1 - Slightly hazardous to water.

# Safety Data Sheet

## Nitrous oxide (refrigerated)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
SDS Reference Number: D-N2O-093B

Kenn-Nr.	: 767
Regulatory reference	: Ensure all national/local regulations are observed. Law on the Protection of Young People at Work (Jugendarbeitsschutzgesetz-JArbSchG) Ordinance on Industrial Safety and Health (BetrSichV) TRBS 3145/TRGS 745 - Transportable pressurized gas containers - Filling, holding, internal transport, emptying TRGS 510 - Storage of hazardous substances in transportable containers TRGS 407 - Activities with gases - Risk assessment TRBS 2141 - Hazards due to steam and pressure - General requirements The Ordinance on Installations for the Handling of Substances Hazardous to Water (AwSV) Storage class according to TRGS 510: 2A Gases (without aerosol dispensers and lighters) Technical Instructions on Air Quality Control (TA Luft). Classification for storage according to TRGS 510: 2A Gase (ohne Aerosolpackungen und Feuerzeuge). TA Luft.

### 15.2. Chemical safety assessment

A CSA has been carried out.

## SECTION 16: Other information

Indication of changes	: Revised safety data sheet in accordance with commission regulation (EU) No 2020/878.
Abbreviations and acronyms	: ATE - Acute Toxicity Estimate. CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008. REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. EINECS - European Inventory of Existing Commercial Chemical Substances. CAS# - Chemical Abstract Service number. PPE - Personal Protection Equipment. LC50 - Lethal Concentration to 50 % of a test population. RMM - Risk Management Measures. PBT - Persistent, Bioaccumulative and Toxic. vPvB - Very Persistent and Very Bioaccumulative. STOT- SE : Specific Target Organ Toxicity - Single Exposure. CSA - Chemical Safety Assessment. EN - European Standard. UN - United Nations. ADR - Agreement concerning the International Carriage of Dangerous Goods by Road. IATA - International Air Transport Association. IMDG code - International Maritime Dangerous Goods. RID - Regulations concerning the International Carriage of Dangerous Goods by Rail. WGK - Water Hazard Class. STOT- RE : Specific Target Organ Toxicity - Repeated Exposure. UFI : Unique Formula Identifier.
Training advice	: None.

# Safety Data Sheet

## Nitrous oxide (refrigerated)

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
SDS Reference Number: D-N2O-093B

Further information : Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).  
Key literature references and sources of data are maintained in EIGA Doc 169 : 'Classification and Labelling Guide', downloadable at <http://www.Eiga.eu>.

Full text of H- and EUH-statements	
Ox. Gas 1	Oxidising Gases, Category 1
Press. Gas (Ref. Liq.)	Gases under pressure : Refrigerated liquefied gas
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H270	May cause or intensify fire; oxidiser.
H281	Contains refrigerated gas; may cause cryogenic burns or injury.
H336	May cause drowsiness or dizziness.

DISCLAIMER OF LIABILITY : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.  
Details given in this document are believed to be correct at the time of going to press.  
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

### Annex to the safety data sheet

#### Table of contents of the Annex

# Exposure scenario

## Nitrous oxide (refrigerated)

Annex to the safety data sheet

Reference number: D-N2O-093B

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

### 1. EIGA093B-2: Professional uses in open conditions.

#### 1.1. Title section

##### Professional uses in open conditions.

ES Ref.: EIGA093B-2

Revision date: 1/31/2017

Processes, tasks, activities covered

Professional uses of a processing aid in non-industrial settings.

##### Environment

##### Use descriptors

CS1

ERC8a

##### Worker

##### Use descriptors

CS2

PROC11

Assessment method

ConsExpo  
EUSES v2.1

#### 1.2. Conditions of use affecting exposure

##### 1.2.1. Control of environmental exposure: ERC8a

ERC8a

Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

##### Product (article) characteristics

Physical form of product

See section 9 of the SDS, No additional information

Concentration of substance in product

≤ 100 %

##### Amount used, frequency and duration of use (or from service life)

No additional information

##### Technical and organisational conditions and measures

# Exposure scenario

## Nitrous oxide (refrigerated)

Annex to the safety data sheet

Reference number: D-N2O-093B

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

Ensure operatives are trained to minimise exposure	
--	--

Conditions and measures related to sewage treatment plant	
No additional information	

Conditions and measures related to treatment of waste (including article waste)	
See section 13 of the SDS. No additional information	

Other conditions affecting environmental exposure	
No additional information	

### 1.2.2. Control of worker exposure: PROC11

PROC11	Non industrial spraying
--------	-------------------------

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure	
Maximum daily site tonnage	0.5
Duration of task	≤ 8 h/day
Exposure duration	Individual events, not totalling more than 1hour, per working day.

Technical and organisational conditions and measures	
General ventilation	
See sections 2 and 7 of the SDS.	
Ensure operatives are trained to minimise exposure. Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
See section 8 of the SDS. Personal protection measures have to be applied in case of potential exposure only.	

# Exposure scenario

## Nitrous oxide (refrigerated)

Annex to the safety data sheet

Reference number: D-N2O-093B

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

### Other conditions affecting workers exposure

Indoor use

### 1.3. Exposure estimation and reference to its source

#### 1.3.1. Environmental release and exposure: ERC8a

The exposure of aquatic, terrestrial, sediment and sewage treatment microorganisms is considered to be negligible because the substance partitions primarily to air when released to the environment, The resulting environmental exposure is not expected to add significantly to already present background levels of the gas in the environment

#### 1.3.2. Worker exposure: PROC11

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Acute - Local - Inhalation	158 mg/m <sup>3</sup>	Indoor use, General ventilation, Without LEV, ConsExpo	

### 1.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

#### 1.4.1. Environment

Guidance - Environment	Check that RMMs and OCs are as described above or of equivalent efficiency
------------------------	--

#### 1.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : ConsExpo model available at: <a href="http://www.rivm.nl/en/Topics/Topics/C/ConsExpo/Spray_model">http://www.rivm.nl/en/Topics/Topics/C/ConsExpo/Spray_model</a>
-------------------	---

## 2. EIGA093B-1: Industrial uses, closed contained conditions

### 2.1. Title section

#### Industrial uses, closed contained conditions

ES Ref.: EIGA093B-1

Revision date: 1/31/2017

Processes, tasks, activities covered	Industrial uses, including product transfers and associated laboratory activities within different closed or contained systems
--------------------------------------	--

# Exposure scenario

## Nitrous oxide (refrigerated)

Annex to the safety data sheet

Reference number: D-N2O-093B

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

Environment	Use descriptors
CS1	ERC4, ERC6b, ERC7

Worker	Use descriptors
CS2	PROC1
CS3	PROC2
CS4	PROC3
CS5	PROC9

Assessment method	MEASE EUSES v2.1
-------------------	---------------------

### 2.2. Conditions of use affecting exposure

#### 2.2.1. Control of environmental exposure: ERC4, ERC6b, ERC7

ERC4	Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
ERC6b	Use of reactive processing aid at industrial site (no inclusion into or onto article)
ERC7	Use of functional fluid at industrial site

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used, frequency and duration of use (or from service life)	
Annual site tonnage:	250
Emission Days (days/year)	365

Technical and organisational conditions and measures	
Soil emission controls are not applicable as there is no direct release to soil. No additional requirement	
Ensure operatives are trained to minimise releases	

# Exposure scenario

## Nitrous oxide (refrigerated)

Annex to the safety data sheet

Reference number: D-N2O-093B

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

### Conditions and measures related to sewage treatment plant

Wastewater emission controls are not applicable as there is no direct release to wastewater

### Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS. No additional information

### Other conditions affecting environmental exposure

No additional information

### 2.2.2. Control of worker exposure: PROC1

PROC1

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions

### Product (article) characteristics

Physical form of product

See section 9 of the SDS, No additional information

Concentration of substance in product

≤ 100 %

### Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.

Duration of task

≤ 8 h/day

Exposure duration

Occasional exposure, e.g. during maintenance and sampling, connecting/ disconnecting containers .

Covers frequency up to:

5 days/week

### Technical and organisational conditions and measures

Handle product within a closed system

During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.

# Exposure scenario

## Nitrous oxide (refrigerated)

Annex to the safety data sheet

Reference number: D-N2O-093B

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

Fill containers at dedicated fill points supplied with local extract ventilation.	
Ensure samples are obtained under containment or extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
See sections 2 and 7 of the SDS.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection measures have to be applied in case of potential exposure only.	
See section 8 of the SDS.	

Other conditions affecting workers exposure	
Indoor use	

### 2.2.3. Control of worker exposure: PROC2

PROC2	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
-------	--

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Duration of task	≤ 8 h/day
Exposure duration	Occasional exposure, e.g. during maintenance and sampling, connecting/ disconnecting containers .

# Exposure scenario

## Nitrous oxide (refrigerated)

Annex to the safety data sheet

Reference number: D-N2O-093B

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

Covers frequency up to:	5 days/week
-------------------------	-------------

Technical and organisational conditions and measures	
Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Fill containers at dedicated fill points supplied with local extract ventilation.	
Ensure samples are obtained under containment or extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
See sections 2 and 7 of the SDS.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection measures have to be applied in case of potential exposure only.	
See section 8 of the SDS.	

Other conditions affecting workers exposure	
Indoor use	

### 2.2.4. Control of worker exposure: PROC3

PROC3	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
-------	--

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

# Exposure scenario

## Nitrous oxide (refrigerated)

Annex to the safety data sheet

Reference number: D-N2O-093B

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

Amount used (or contained in articles), frequency and duration of use/exposure	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Duration of task	≤ 8 h/day
Exposure duration	Occasional exposure, e.g. during maintenance and sampling, connecting/ disconnecting containers .
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures	
Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Fill containers at dedicated fill points supplied with local extract ventilation.	
Ensure samples are obtained under containment or extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
See sections 2 and 7 of the SDS.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection measures have to be applied in case of potential exposure only.	
See section 8 of the SDS.	

Other conditions affecting workers exposure	
Indoor use	

# Exposure scenario

## Nitrous oxide (refrigerated)

Annex to the safety data sheet

Reference number: D-N2O-093B

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

### 2.2.5. Control of worker exposure: PROC9

PROC9	Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
-------	---

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Duration of task	≤ 8 h/day
Exposure duration	Occasional exposure, e.g. during maintenance and sampling, connecting/ disconnecting containers .
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures	
Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Fill containers at dedicated fill points supplied with local extract ventilation.	
Ensure samples are obtained under containment or extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
See sections 2 and 7 of the SDS.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

# Exposure scenario

## Nitrous oxide (refrigerated)

Annex to the safety data sheet

Reference number: D-N2O-093B

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection measures have to be applied in case of potential exposure only.	
See section 8 of the SDS.	

Other conditions affecting workers exposure	
Indoor use	

### 2.3. Exposure estimation and reference to its source

#### 2.3.1. Environmental release and exposure: ERC4, ERC6b, ERC7

The exposure of aquatic, terrestrial, sediment and sewage treatment microorganisms is considered to be negligible because the substance partitions primarily to air when released to the environment, The resulting environmental exposure is not expected to add significantly to already present background levels of the gas in the environment

#### 2.3.2. Worker exposure: PROC1

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Inhalation - Long-term - systemic effects	0.018 mg/m <sup>3</sup>	Indoor use, General ventilation, Without LEV, MEASE	0

#### 2.3.3. Worker exposure: PROC2

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Inhalation - Long-term - systemic effects	14.937 mg/m <sup>3</sup>	Indoor use, General ventilation, Without LEV, MEASE	0.082

#### 2.3.4. Worker exposure: PROC3

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Inhalation - Long-term - systemic effects	37.342 mg/m <sup>3</sup>	Indoor use, General ventilation, Without LEV, MEASE	0.204

#### 2.3.5. Worker exposure: PROC9

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Inhalation - Long-term - systemic effects	74.683 mg/m <sup>3</sup>	Indoor use, General ventilation, Without LEV, MEASE	0.408



# Exposure scenario

## Nitrous oxide (refrigerated)

Annex to the safety data sheet

Reference number: D-N2O-093B

CAS-No.: 10024-97-2 Product form: Substance Physical state: Gas

### 2.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

#### 2.4.1. Environment

Guidance - Environment	Check that RMMs and OCs are as described above or of equivalent efficiency
------------------------	--

#### 2.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : MEASE model available at: <a href="http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php">http://www.ebrc.de/industrial-chemicals-reach/projects-and-references/mease.php</a>
-------------------	--

**End of document**